

XP-N160II

Thermal Receipt Printer

XP-N160II is an economic model with USB or Lan port, with auto cutter.

Column capacity : 576 dots/line 512 dots/line

Printing speed : 160mm/s

Interface : USB / Lan

Printing paper : $79.5 \pm 0.5\text{mm} \times \phi 80\text{mm}$

Line spacing : 3.75mm (Adjustable by commands)



Printing

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	160mm/s
Interface	USB / Lan
Printing paper	$79.5 \pm 0.5\text{mm} \times \phi 80\text{mm}$
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/
	Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: $1.5 \times 3.0\text{mm}$ (12×24 dots) Font B: $1.1 \times 2.1\text{mm}$ (9×17 dots) Chinese,traditional Chinese: $3.0 \times 3.0\text{mm}$ (24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Barcode Character

Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128 / QR CODE

Buffer

Input buffer	64 K Bytes
NV Flash	256k bytes

Power

Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	0.98KG
Dimensions	184.5×145×153mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)
Reliability	
Cutter life	1million cuts
Printer head life	50KM