



- ◆ Integrated board, higher reliability, more durable
- ◆ Support GB18030 Font, multiple International Languages
- ◆ Rich communication interface, intelligent voice prompt, simple operation
- ◆ Support network printing status monitoring, computer multi-connection printing.
- ◆ Embedded web page, directly through the IE to configure the printer
- ◆ Support for driving high-speed download printing.



Model	GP-D801
Print speed	250mm/s
Paper roll	79.5 ±0.5 mm
Dot density	576 dots/line; 512 dots/line
Character size	ANK Font, Font A : 12×24dots Font B : 9×17mm (9×17 dots) Simplified/Traditional Chinese : 24×24dots
Font	Standard GB18030
Print command	Compatible with ESC/POS emulation
Interface	USB+ Ethernet/USB+ Ethernet+Bluetooth/USB+Ethernet+Bluetooth+Audio/USB+Ethernet+WIFI
Reliability	150km
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/ITF/CODABAR/CODE39/CODE93/CODE128/QRCODE
Paper thickness	0.06~0.08mm
Input buffer	800KB~1MB
NV Flash	256KB
Adapter	outside
Adapter output	AC 110V/220V , 50~60Hz
Adapter input	DC 24V/2.5A
Printer input	DC 24V/2.5A
Cashdrawer out	DC 24V/1A
Work Environment	Temperature: 5℃ ~ 45℃ ; Humidity: 10 ~ 80%
Storage Environment	Temperature: -10℃ ~ 50℃ ; Humidity: 10 ~ 90%
Dimensions	204*147*138mm (W*D*H)

APPLICATIONS



Catering industry



Supermarket



Warehousing



Shopping mall



Retail



Medical